



**STOPS RUST
GRAFFITI REMOVER**

DESCRIPTION AND USES

Rust-Oleum® Graffiti Remover is designed to remove graffiti without causing damage to the original surface. It removes spray paint, crayons, markers, and ink from hard surfaces such as metal, vinyl siding, wood, plastic, aluminum, fiberglass, ceramic and brick. The any-angle spray feature allows you to spray in any direction, even upside-down. Comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying. Use on garage doors, cinder block, road signs, washroom stalls, sidewalks, buildings, vehicles, railway bridges and underpasses.

PRODUCTS

SKU	Description
260844	Graffiti Remover

PRODUCT APPLICATION

APPLICATION

Wear gloves to protect skin. Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake can often during use. Hold can upright 6-10" from surface and spray in a steady back-and-forth motion. Keep the can in motion while spraying. Allow the product to sit for a few minutes before wiping off with a clean cloth.

FOR PAINTED SURFACES: Leave product on for 30 seconds and wipe off with a cloth or flush with a strong stream of water. If left on too long it may dull or damage original surface. When using on synthetic surfaces (or surfaces susceptible to solvent damage such as rubber, asphalt tile and plastics) pre-test in an inconspicuous area first.

PRODUCT APPLICATION (cont.)

FOR POROUS SURFACES: First wet the surface with clean water. Leave product on for several minutes before wiping clean with a cloth or stream of water. Use a cloth or stiff brush to help remove graffiti.

FOR STUBBORN STAINS: Apply product and let stand for 5 minutes. Use a stiff brush before flushing with water. Repeat as needed. For all surfaces allow product to work longer when temperatures are below 50°F (10°C). For best results, use on freshly painted graffiti. Do not use near open flame.

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.



TECHNICAL DATA

STOPS RUST GRAFFITI REMOVER

PHYSICAL PROPERTIES

	GRAFFITI REMOVER
Solvents	Acetone, Diacetone alcohol, Isopropyl alcohol, Xylene
Fill Weight	11 ounces
Shelf Life	5 years
Flash Point	-156°F (-104°C)
Safety Information	For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.